

EPS DEPOT INC

Material Safety Data Sheet(MSDS)

Section.1: Substance Identity Company Information

Product Name: Expanded Polystyrene (EPS) Foam
Manufacturer: EPS Depot Inc.
2455 Milltower Court
Mississauga Ont.
L5N 5Z6

Section.2: Chemical Compositions

Ingredient	CAS No. Approx.	Weight Percentage
Benzene, Ethenyl-, Homopolymer	9003-53-6	>98%
Hexabromocyclododecane (Fire Retardant)	3194-55-6	<1%
Pentane	109-66-0	<1%

Chemical Name/Synonyms: Modified EPS, Modified Foam Polystyrene
Chemical Family: Ethenylbenzene Homopolymer

Section.3: Hazard Identification

Primary route(s) of entry into body: Inhalation and ingestion

Acute effects:

Eyes: Dust particles may cause mechanical irritation.

Skin: Irritation from skin contact is rare. Direct contact may cause slight skin irritation in few.

Inhalation: May cause respiratory discomfort similar to inhalation of too much "inert" dust.

Ingestion: Biologically inert.

Chronic effects in humans: No known adverse effects.

Section.04. First Aid Measures

Eye contact: Hold eyelids open and flush immediately with gentle stream of water for at least 15 minutes.

Seek medical attention if irritation persists.

Skin contact: Wash exposed areas with mild soap and water.

Inhalation: Move person to fresh air. If breathing is difficult seek medical attention.

Ingestion: Not likely to cause serious injury if ingested.

Section.5: Fire Fighting Measures

Flash Pt. and Method Used: 6750 F (ASTM D-1929 per bead manufacturers)

Special Fire fighting Instructions: Use self-contained breathing apparatus respirator and approved personal protective clothing.

Extinguishing Media: Water fog, carbon dioxide, foam and dry chemical.

Auto-Ignition Temperature: 8800 F (ASTM D-1929 per bead manufacturers)

Unusual Fire and Explosion Hazards: Combustion causes dense, black smoke. Smoke consists of carbon monoxide, carbon dioxide and styrene. Other undetermined hydrocarbon fractions could be released in small quantities.

Section.6: Accidental Release Measures

Spill or leak procedures: Pickup or if material is in small pieces, sweep up and place in suitable container for disposal

Reportable Quantity: None

Disposal Method: Recycle, incinerate with waste heat recovery, or landfill in accordance with federal, state and local regulations.

Section.7: Handling and Storage

Storage: Although expanded polystyrene contains a fire retardant additive, it is considered combustible and adequate protection from sources of ignition should be taken.

Section.8: Exposure Controls and Personal Protection

Personal protective equipment:

Respiratory Protection: Use approved dust mask when sawing or sanding

Gloves: none required

Eye Protection: Use approved safety glasses/goggles when sawing or sanding.

Section.9: Physical and Chemical Properties

Appearance: Rigid blocks or boards

Odor: Slight hydrocarbon odor.

Physical state: Solid

Color: White

Boiling Point: Not Applicable

pH: Not Applicable

Melting Point: Not Applicable (softening begins at 1600 F)

Volatiles by Volume: <2

Vapor Density (Air=1): Not Applicable

Evaporation Rate: None

Solubility in water: Insoluble

Specific gravity: <1

Section.10: Stability and Reactivity

Stability: The product is stable.

Conditions to Avoid: Fire and high temperatures.

Incompatibility: Hydrocarbons, esters, insecticides, amines and aldehydes.

Hazardous polymerization: None.

Hazardous decomposition: Carbon monoxide, acid gases, water, carbon dioxide, carbon.

Section.11 Toxicological Information

Ventilation: No special ventilation requirements

Personal protective equipment:

Respiratory Protection: Use approved dust mask when sawing or sanding

Gloves: none required

Eye Protection: Use approved safety glasses/goggles when sawing or sanding.

Section.12: Ecological Information

Biologically Inert

Section.13: Disposal Consideration

Non hazardous waste. Dispose of material according to local, state, federal regulations.

Section.14:Transport Information

Not a "Hazardous Material"

Section.15: Regulations

CAN/ULC-S701-11: Listed

Section.16: Other Information

Expanded Polystyrene materials sold for construction use have a fire retardant modifier but are considered combustible, as are all organic materials. They must not be stored or installed near open flame or any other source of ignition. In addition, when EPS insulation is installed in the interior of a structure it must be protected by a proper thermal barrier, and the installer must review applicable local, state and federal building codes to determine the correct thermal barrier for the particular application

The information in the MSDS was obtained from sources which we believe are reliable. However the information is provided without any warranty, express or implied, regarding it's correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Date of Preparation: Apr.14.2014